




PRODUCT DATA SHEET



A) SPECIFICATIONS

- 1 Shell: Stainless steel.
- 2 Hexagon socket head Screw: Stainless steel VCI 5x20
- 3 Gasket: Rubber EPDM.
- 4 16 sqmm Connection cable: L=500 PE flexible copper cable.
- 5 Cable lug Ø8: Tinned copper. Including earthing screw kit (screw VCI 8x20; nut DAI 8, washers REG 8 + RPI 8/16).
- 6 Inner Contact: Tinned brass.
- 7 Contact bar: Tinned brass.

B) RESISTANCE TESTS

Waterproof test:

IP 68 (FIMO Test according to IEC60529 normative).

Contact Resistance $\leq 1\text{mOhm}$

Operating Temperature $-40^{\circ}\text{C} +85^{\circ}\text{C}$

C) PACKAGING INFORMATION

Packing in boxes.

Label indicating:

product code, article, quantity,

production batch,



FIMO logo and figure.

(Customer code on request).

D) MOUNTING INSTRUCTIONS

IST 046

code	6115409009.16
article	KMT 9 P E

D	L		
8-9	500	10	0.1875kg

RI	DATE	DR	DATE	AP	Description: Grounding Kit
02					
01					
00	31/07/2017	E.B.	31/07/2017	A.V.	
1 ST EMISSION					Use: Earthing of coaxial cables.
